



Chain Slings and Accessories


Offering Safety Material

Connecting Links

- Forged Alloy Steel (Quenched and Tempered) material
- For use with Alloy Chain Grade 80 and Wire Rope for lifting application
- Embossed with OSM, Traceability Code, WLL & Product Code
- Working Load Limit at 4:1
- Proof Load at 2.5 times of Work Load Limit
- Fatigue rated at 1.5 times the WLL with 20,000 cyclic test
- Identical sides for easy assembly



Type: LCT




Eye Sling Hooks

- Forged Alloy Steel (Quenched and Tempered) material
- For use with Alloy Chain Grade 80 and Wire Rope for lifting application
- Embossed with OSM, Traceability Code, WLL & Product Code
- Working Load Limit at 4:1
- Proof Load at 2.5 times of Work Load Limit
- Fatigue rated at 1.5 times the WLL with 20,000 cyclic test
- Incorporated with Latch to provide additional lifting safety
- Stainless Steel Spring is used to prevent rust



Type: HEL



Alloy Connecting Link Grade 80 Type: LCT

Product Code	Size mm	L mm	B mm	C mm	E mm	G mm	Weight kg	WLL mm
LCT 006	6	44	15	37	58	7	0.14	1.2
LCT 007	7-8	59	18	48	75	9	0.20	2
LCT 010	10	68	25	61	89	13	0.38	3.2
LCT 013	13	91	30	76	116	16	0.76	5.4
LCT 016	16	100	36	93	144	19	1.10	8.0
LCT 018	18-20	122	42	109	170	23	1.80	12.8
LCT 022	22	152	49	128	192	24	3.20	16.0
LCT 026	26	162	55	150	220	31	4.50	20.6
LCT 032	32	202	69	192	281	38	9.00	32.8

Alloy Eye Sling Hook Grade 80 c/w Latch Type: HEL

Product Code	Size mm	L mm	B mm	E mm	F mm	G mm	H mm	Weight kg	WLL 4:1 Ton
HEL 006	6	108	24	20	9	16.5	20	0.25	1.2
HEL 007	7-8	132.5	30	25	11	19.5	23	0.40	2
HEL 010	10	167.5	34	38	15	20	31	0.92	3.2
HEL 013	13	213.5	39	43	19	31	38	2.15	5.4
HEL 016	16	255	46	50	23	36	47	2.97	8.0
HEL 020	20	304	59	62	24	52	48	6.36	12.5
HEL 022	22	348	71	62	32	54	74	8.20	15.0
HEL 026	26	394	100.5	64	35	60	80	13.0	20.8
HEL 032	32	480	102	88	37	60	91	18.0	32.8