


## 4XSeS(39)+FC



For Crane, Hoist and Piling Purposes  
 Construction:  
 4 Strands  
 39 Wires per Strand  
 1 Fiber Core

Diameter of Rope		Diameter of Outer Wires	Area	Breaking Load in Metric Tons			Aprox. Weight Per Meter
mm	Approx.inch	mm	mm <sup>2</sup>	S	H	SH	kg/m
8.0	5/16	0.56	28.7	3.83	4.18	4.53	0.261
9.0	3/8	0.63	36.4	4.83	5.28	5.72	0.330
10.0	13/32	0.71	44.9	5.98	6.52	7.06	0.408
11.2	7/16	0.80	56.3	7.50	8.19	8.87	0.512
12.0	15/32	0.85	64.7	8.32	9.08	9.84	0.588
12.5	1/2	0.90	70.2	9.35	10.2	11.1	0.638
14.0	9/16	1.00	88.0	11.7	12.8	13.9	0.800
16.0	5/8	1.12	115	15.3	16.7	18.1	1.04
18.0	23/32	1.25	145	19.4	21.2	23.0	1.32
19.0	3/4	1.32	162	21.6	23.6	25.6	1.47
20.0	13/16	1.40	180	23.9	26.1	28.3	1.63
(22.0)		1.57	217	28.9	31.6	34.2	1.97
22.4	7/8	1.60	225	30.0	32.8	35.5	2.05
(24.0)	15/16	1.70	259	33.2	36.3	39.3	2.35
25.0	1	1.80	281	37.3	40.7	44.1	2.55
(25.0)	11/32	1.85	303	40.3	44.0	47.6	2.76
26.0	1 1/8	2.00	352	46.9	51.2	55.4	3.24
28.0	1 3/16	2.12	405	53.8	58.7	63.6	3.73
30.0	1 1/4	2.24	445	59.3	64.7	70.1	4.10
31.5	-	2.27	457	-	66.8	72.3	4.12
32	1 5/16	2.36	506	67.1	73.2	79.3	4.64
s33.5	1 13/32	2.50	568	75.4	82.52	89.0	5.21
34	1 1/2	2.65	634	84.1	91.7	99.3	5.81
35.5	1 9/16	2.80	718	93.8	102	110	6.61
36	1 11/16	3.00	811	106	115	125	7.46
38	1 3/4	3.15	909	119	129	140	8.37